BOUNDARY LINE ADJUSTMENT SURVEY FOR FOUND 5/8" REBAR JODY MECHAM and TRENT BOLTON FOUND 1/2" REBAR IN AT SECTION CORNER STONE MOUND AT 1/4 ON PREVIOUS SURVEY S 89°45'16" E 2637.11' CORNER ON PREVIOUS POSITION OF CORNER DETERMINED BY OTHERS SURVEY SECTION 1, TOWNSHIP 2 SOUTH, RANGE 2 WEST SEC 35 \$ SEC 36 S 89°45'16" E S 89°45'16" E SEC 36 SEC 31 S 89°45'16" E SEC 2 SEC 1 1318.55 1318.55 1318.56 1316.86 SEC 1 SEC 6 UINTAH SPECIAL BASE AND MERIDIAN FOUND COUNTY MONUMENT AT SECTION CORNER DESCRIPTION OF PARCEL A Commencing at the East Quarter Corner of Section 1, Township 2 South, Range 2 West of the Uintah Thence South 89°50'12" West 1355.07 feet along the South line of the NE1/4 of said Section to the TRUE POINT OF BEGINNING; Thence South 89°50'12" West 622.82 feet along said South line to the West line of the E1/2 of the SW1/4 of said NE1/4; Thence North 00°15'43" West 1409.66 feet to the Northwest Corner of said E1/2; Thence North 89°54'17" East 230.00 feet along the North line of said E1/2; Thence South 00°15'43" East 330.00 feet; SCALE:1"=300' Thence North 89°54'17" East 290.00 feet; Thence North 00°15'43" West 330.00 feet to said North line; Thence North 89°54'17" East 103.26 feet along said North line; Thence South 00°14'38" East 1408.92 feet to the TRUE POINT OF BEGINNING, containing 17.96 acres. Said parcel being subject to that portion being used as County Road right-of-way. LINE BEARING DISTANCE L1 S 89.50'11" W 123.00 L7 S 89 50 17 W 123.00

L2 N 00°00'00" W 485.95'

L3 N 90°00'00" E 25.00'

L4 S 00°00'00" E 922.44'

L5 S 00°15'43" E 330.00'

L6 N 89°54'17" E 290.00'

L7 N 00°15'43" W 330.00' DESCRIPTION OF PARCEL B Commencing at the East Quarter Corner of Section 1, Township 2 South, Range 2 West of the Uintah Special Base and Meridian; Thence South 89°50'12" West 880.28 feet along the South line of the NE1/4 of said Section to the TRUE POINT OF BEGINNING; N 89°54'17" E 2636.18' Thence South 89°50'12" West 474.79 feet along said South line; FOUND 1/2" REBAR L8 N 89°54'17" E Thence North 00°14'38" West 1408.92 feet to the North line of the S1/2 of said NE1/4; Thence North 89°54'17" East 505.79 feet along said North line; AT 1/16 CORNER 1317.63 1318.55' 1318.72' 1318.72' Thence South 00°00'00" East 922.44 feet; 518.44 329.41 Thence North 90°00'00" West 25.00 feet; 290.00' N 89°54'16" E 2637.44' 230.00 505.79 POSITION OF CORNER 659.27' Thence South 00°00'00" East 485.95 feet to the TRUE POINT OF BEGINNING, containing 15.98 acres. DETERMINED BY OTHERS Said parcel being subject to that portion being used as County Road right-of-way. PARCEL C DESCRIPTION OF PARCEL C 14.74 Acres Commencing at the East Quarter Corner of Section 1, Township 2 South, Range 2 West of the Uintah LEGEND AND NOTES Thence South 89°50'12" West 452.65 feet along the South line of the NE1/4 of said Section to the PARCEL B TRUE POINT OF BEGINNIN FOUND SECTION CORNER (AS DESCRIBED ON PLAT) Thence South 89°50'12" West 427.63 feet along said South line; 15.98 Acres Thence North 00°00'00" West 485.95 feet; FOUND 1/4 CORNER (AS DESCRIBED ON PLAT) Thence North 90°00'00" East 25.00 feet; PARCEL A Thence North 00°00'00" West 922.44 feet to the North line of the S1/2 of said NE1/4; ♦ FOUND 1/16 CORNER SET OR DETERMINED BY OTHERS APPROXIMATE Thence North 89°54'17" East 518.44 feet along said North line; HOUSE LOCATION Thence South 00°17'34" East 554.50 feet; O FENCE POST USED AS PROPERTY CORNER Thence South 89°50'11" West 123.00 feet; Thence South 00°17'32" East 853.20 feet to the TRUE POINT OF BEGINNING, containing 14.74 acres. SET 5/8"X24" REBAR WITH PLASTIC CAP STAMPED Said parcel being subject to that portion being used as county road right-of-way. "ALLRED SURVEYING" SET BY THIS SURVEY - × - EXISTING FENCE LINE OWNER'S CERTIFICATE We, the undersigned, owners of the parcels of land shown hereon, do hereby change, adjust, place and DRIVEWAY fix our mutual boundary lines to the positions indicated and described on this plat. Date Acknowledged Notary's Print Name Landowner's Signatures FENCE to Notary Initials 622.82 452.65 659.30' N 89°50'12" E 2637.85' ON PREVIOUS SURVEY CAP AT 1/4 CORNER 1318.59 2637.19' 2500 NORTH (COUNTY ROAD #157) 5275.03' N 89°50'12" E ACKNOWLEDGMENT State of Utah DUCHESNE COUNTY TREASURER County of Duchesne \$SS PROPERTY TAX CLEARANCE On the dates shown by each signature, personally appeared before me the signers of the above certificate who duly acknowledged to me that they did execute same. THIS______ OF 20 ____. My commission expires_____ Notary Public STEPHEN POTTER DUCHESNE COUNTY TREASURER SURVEYOR'S CERTIFICATE I, JERRY D. ALLRED, DUCHESNE COUNTY, UTAH, DO HEREBY CERTIFY THAT I AM A PROFESSIONAL LAND SURVEYOR AND THAT I HOLD CERTIFICATE NUMBER 148951 AS PRESCRIBED BY THE STATE OF UTAH. I FURTHER CERTIFY THAT THIS PLAT WAS PREPARED FROM THE FIELD NOTES AND ELECTRONIC DATA DUCHESNE COUNTY PLANNING COLLECTOR FILES OF AN ACTUAL SURVEY MADE BY ME OR UNDER MY PERSONAL SUPERVISION AND THAT THE MONUMENTS INDICATED WERE FOUND OR SET DURING SAID SURVEY, AND THAT THIS PLAT ACCURATELY The purpose of this survey is to adjust and change the boundary lines of the three parcels shown DEPARTMENT APPROVAL as A, B, and C on this plat owned by Trent and Natalie Bolton. This survey represents a dependant REPRESENTS SAID SURVEY TO THE BEST OF MY KNOWLEDGE AND BELIEF. APPROVED AS A BOUNDARY LINE ADJUSTMENT ON THIS resurvey of certain portions of Section 1 as shown on the notes and plat of the original surveys performed by the General Land Office. It was found that multiple surveys have been performed in _____DAY OF _____OF 20___. this section and have attempted to perpetuate the PLSS (Public Land Survey System) Corners at their true positions. Section 1 was originally surveyed using the Statutory Subdivision Breakdown method. This survey attempts to follow this procedure. The monuments found and used to represent the corners originally set are based on those evidences of said "G.L.O." surveys to the best of my knowledge. Descriptions of the monuments found and used are shown on this plat at MICHAEL HYDE DUCHESNE COUNTY COMMUNITY DEVELOPMENT their respective locations. Jerry D. Allred, Professional Land Surveyor Utah Certificate Number 148951 BASIS OF BEARINGS THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM PROCEDURES AND EQUIPMENT THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. COUNTY RECORDER'S CERTIFICATE OBSERVATIONS USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER STATE OF UTAH COUNTY OF DUCHESNE } SS THIS IS TO CERTIFY THAT THIS PLAT WAS FILED FOR RECORD IN THE COUNTY RECORDER'S OFFICE ON THE _____, 20___, AT_____O'CLOCK__M, AND IS DULY RECORDED. COUNTY RECORDER FOUND HARROW TOOTH AT CLOSING CORNER SEC 6 FOUND DUCHESNE COUNTY MONUMENT ON PREVIOUS SURVEY N 89°50'00" E 2638.91' N 89°50'00" E 2638.91' SEC 12 SEC 11 \$ SEC 12 FOUND COUNTY MONUMENT FOUND COUNTY MONUMENT AT SECTION CORNER JERRY D. ALLRED & ASSOCIATES, INC. AT SECTION CORNER SURVEYING CONSULTANTS 1235 NORTH 700 EAST--P.O. BOX 975 DUCHESNE, UTAH 84021 5 JUN 2017 17-100-032 (435) 738-5352

3